



the
nanoGard

TECHNICAL DATA SHEET

High Performance Solar Series

FEATURES:

- UVA and UVB heat rejection for 100% UV heat rejection.
- Clear-film technology with outstanding heat rejection to create the perfect film for high end cars.
- Maintains original appearance of your car. Light films allows upto 85% of sunlight into the cabin, while filtering 100% of its damaging rays.
- Improved safety while driving, reducing glare and increasing visibility.
- Improves cabin comfort, reduces demand on AC systems by rejecting up to 80% of solar heat-gain.
- Increased fuel-efficiency and Eco-friendliness 3% savings on your MPG's.
- Protects interior from fading while maintaining the exterior image of your car.

High Performance Solar Series

Product	VLT%	UVR%	(Int/Ext)	IRR%	TSER%	Thick (MIL)
			VLR%			
HPS80	85	100	07/07	90	67	3
HPS70	70	100	07/07	90	70	3
HPS50	50	100	08/08	90	78	3
HPS30	30	100	09/09	90	81	3
HPS20	20	100	09/09	90	87	3

All figures are measured by **ASTM** regulations

PRODUCT BY:



the
nanoGard

The Nano Gard LLC
1603 Capitol Ave
Cheyenne, WY 82001
www.thenanogard.com
info@thenanogard.com